

# 2009 Lido Class Championship Regatta Measurement Checklist

Skipper's Name \_\_\_\_\_ Hull # \_\_\_\_\_

Boat Owner's Name (if different) \_\_\_\_\_ Sail # \_\_\_\_\_

This checklist is to be completed by your Fleet Measurer and submitted at Registration/Check-in. If you do not have a Fleet Measurer, you may have your checklist completed by any Fleet Measurer, the Chief Measurer or their proxies. Those that cannot locate an eligible measurer shall make an appointment with the Chief Measurer to have their checklist completed at the Championship Regatta.

Chief Measurer Walter Johnson can be reached at [hojosails@aol.com](mailto:hojosails@aol.com) and cell phone (562) 397.0976. Please check off each box to show compliance.

## Document Verifications:

- Official Certificate of Measurement and registration is complete and dated
- 2008 Lido 14 Class Association boat decal is on the boat transom

## Sail Verifications

- Measurement mark, measurer initials, and measurement date on each sail
- Lido 14 royalty tags attached
- Honor Awards attached to mainsail(s)
- Correct sail number attached to mainsail(s)

## Boat/Equipment Verifications

Verify compliance of the following items to the Class measurement rules.

- 1 Boat weight \_\_\_\_\_ pounds + \_\_\_\_\_ pounds ballast = 310 pounds minimum (Boat will be weighed at MBYC)
- 2 Mast fore/aft position (48-3/4" to 49-1/4")
- 3 Jib tack pin less than 3 3/4" from deck
- 4 Jib fairlead aft position (95" minimum)
- 5 Jib fairlead span (64-3/4" minimum)
- 6 Rudder width 9-3/4" to 10-1/4" measured below extension of hull at transom
- 7 Rudder depth/length measured down from leading edge at the extension of hull at transom (23-3/4" to 24-1/4")
- 8 Rudder thickness (5/8" to 7/8")
- 9 Rudder angle (27" minimum)
- 10 Whisker pole length (72" maximum)
- 11 Mainsheet bridle traveler height (22" maximum)
- 12 Centerboard slot width (1-1/8" minimum)
- 13 Centerboard width 12-5/8" to 13-1/8" @ 44" from tip and 11-5/8" to 12-1/8" @ 8" from tip.
- 14 Centerboard thickness (3/4" to 1")
- 15 Centerboard gybe (1/4" maximum)
- 16 Centerboard depth (47-1/2" to 48-1/2") or pivot position (per by laws ART XIII 5. (c) (5) for hull numbers less than 3449)
- 17 Centerboard fore/aft position (95" +/- 1/2" or per by laws ART XIII 5. (b) (5) for hull numbers less than 3449)

I am the Fleet Measurer to the Fleet to which this member belongs, or a Certified Measurer authorized by the Chief Measurer and the Governing Board to verify the above measurements.

Measurer or Chief Measurer Designate (signature) \_\_\_\_\_ Date \_\_\_\_\_

Measurer or Chief Measurer Designate (Print) \_\_\_\_\_

**IMPORTANT:** This document may be completed if necessary by a Certified Measurer or the Official Measurement Committee and turned in at Check-In at *the* Regatta Site. If your fleet measurer is unavailable, or you are an unattached member or repairs are necessary to make the boat compliant in time for the early signup in due date of July 24, 2009. Make a copy of the incomplete document for reference and retain it with your Measurement Certificate for presentation at the Mission Bay Yacht Club Registration Desk